



LGR 2800i

Simply Brilliant. Dominant Performance.

The LGR 2800i refrigerant dehumidifier offers exceptional performance across the full range of jobsite conditions – in low humidity environments and even at high temperatures (up to 125°F). The unit is engineered for the heavy demands of water damage restoration and rental use. A rugged rotomolded housing and durable construction make this Dri-Eaz dehumidifier a top choice for professionals everywhere.

The LGR 2800i provides high performance with low energy consumption - 130 pints per day (at AHAM) with just 8 amps, as verified by a laboratory under contract to AHAM.

Product Features

- Built-in thermo-hygrometer monitors and displays inlet and outlet conditions.
- Automatic humidistat control.
- Automatic high temperature mode – no manual adjustments required.
- Outstanding performance at only 8 amps.
- HygroTrac-ready – track dehumidifier performance automatically on the HygroTrac website
- Drip pan has built-in Microban® antimicrobial product protection to inhibit the growth of odor and stain causing bacteria, mold and mildew.
- Legendary Dri-Eaz rotomolded housing resists dents and scratches – and is easy to keep looking new.



Item #F410

Product Specifications

Model	LGR 2800i – F410
Power	8 amps, 115 volts
Water removal AHAM (80°F/60% RH)	130 pints 61.5 liters / day
Water removal max. (90°F/90% RH)	200 pts. 94.6 liters / day
Water removal min. (80°F/20% RH)	20 pts. 9.5 liters / day
Max. process air	400 CFM 679.7 CMH*
Air filter	3M HAF filter (Dri-Eaz part no. F421)
Dimensions (H x D x W)	40.5 x 23 x 24 in. 103 x 58 x 61 cm
Use weight	160 lbs. 72.6 kg
Power cord	25 ft. 7.6 m detachable
Hose	40 ft. 12.2 m
Construction	Rotomolded polyethylene shell
Safety	ETL certified to UL 474 and CSA 22.2 no. 92
*Automatic variable speed for optimized performance.	

Distributed By:



www.onesourcerental.com