



MH-0190-0M10

Frame: Rugged steel body · Extension cord wrap · Powder coated hood and fuel tank · Powder coated steel handles for easy lifting · 10-inch pneumatic tires · Spare parts storage system (located on back of unit) · Fuel drain plug

Burner Head: Clamped hoses · Secured photo cell · 1-piece cast aluminum · Secured fully insulated ignition connection

Motor: Heavy-duty, high quality cast aluminum enclosed electric motor

Components: Built-in temperature control thermostat with control dial and digital temperature read-out · High performance fan · Power switch · Secured internal components · Integral overheat and flame-out safety · Fuel gauge · Integrated fuel pressure gauge · Oversized fuel cap · High limit temperature shut-off · Sure start ignition for cold temperature starts · Dual connector ignitor · Error indicator read-out

Factory tested for multiple fuels: Kerosene, JP8/Jet A fuel, No. 1 or No. 2 fuel oil and No. 1 or No. 2 diesel fuel

For use in workshops, warehouses, garages, construction sites and farms with proper ventilation.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations, and/or ordinances.

Please see heater “Owner’s Manual” included with each heater for a complete list of important safety information.

Important Notes:

- Not for use in residential living areas or inadequately ventilated areas.
- Proper ventilation required during operation.
- Must be plugged into an approved standard electrical outlet for operation

Specifications	
Air Pump Pressure	7.5 PSI
AC Power	120 Volt/60Hz/2.7 Amp
Heat Output	190,000 BTU
Hot-Air Flow	630 CFM
Max. Operating Hours	9.7 hours
Motor Size	1/4 HP
Fuel Tank Capacity	13.0 gallons
Fuel Consumption	1.34 gal./hr.
Heating Area	4,300 sq. ft.
Multi-Fuel Capable	Yes
Weights & Dimensions	
Net Weight	58 lbs.
Shipping Weight	65 lbs.
Length	42 in.
Width	24 in.
Height	26 in.

Distributed By:



www.onesourcerental.com