

Distributed By:



www.onesourcerental.com

ROL-A-LIFT SPECIFICATIONS (Made in U.S.A.)

	Standard Model Specifications						
	M-2 & M-2W (1 pair)	M-4 & M-4W (1 pair)	M-4-6 & M-4-6W (1 pair)	M-6 & M-6W (1 pair)	M-8 & M-8W (1 pair)	M-10 & M-10W (1 pair)	M-12 & M-12W (1 pair)
<b>Capacity Per Pair</b>	2,000#	4,000#	4,000/6,000#	6,000#	8,000#	10,000#	12,000#
<b>Max. Hydraulic Lift</b>	4-1/2"	12-3/16"	12-3/16" / 6"	4-3/4"	4-3/4"	4-3/4"	4-3/4"
<b>Type of Lift</b>	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
<b>Standard Wheels</b>	Phenolic	Phenolic	Phenolic	Phenolic	Semi-Steel	Semi-Steel	Forged-Steel
<b>Wheel Size</b>	5" x 2"	6" x 2"	6" x 2"	6" x 2"	8" x 2-1/2"	8" x 3"	8" x 2-1/2"
<b>Overall Height</b>	47-1/2"	44"	44"	42-1/2"	45"	45-1/2"	45-1/2"
<b>Overall Width</b>	22"	23"	23"	23"	23-1/8"	24"	24"
<b>Caster Centers</b>	18"	18"	18"	18"	18"	18"	18"
<b>Overall Depth</b>	12-1/2"	16-1/2"	16-3/4"	16-3/4"	17-1/4"	18"	18"
<b>Forks Adjustable</b>	7-1/4"-17-1/2"	5"-19-1/2"	6"-19-1/2"	6"-19-1/2"	7-1/4"-19-1/2"	9-1/4"-19-1/2"	9-1/4"-19-1/2"
<b>Fork Length</b>	5"	6"	6"	6"	6"	6"	6"
<b>Fork Thickness</b>	3/4"	1-1/8"	1-1/8"	1-1/8"	1-1/8"	1-1/8"	1-1/8"
<b>Weight Per Pair (Standard)</b>	160#	325#	340#	335#	400#	438#	470#
<b>Weight Per Pair (Wide)</b>	230#	415#	430#	425#	490#	520#	530#