

SAFE TOUGH RELIABLE

3 YEAR
WARRANTY

IX400

SPECIFICATIONS

Heat Capacity	400,000 BTU/HR
Fuel Consumption NG/P	400 CFH / 18.5 lbs/h
Power Requirements	115V/60Hz/1PH/12A
Heat Exchanger	20ga SS304
Combustion Chamber	18ga SS304
Dimensions	82"L x 29"W x 58.5"H
Net Weight	560 lbs
Temperature Rise (w/o Duct)	90°C
Temperature Rise (w/ Duct)	100°C
Max Heated Air Flow (w/o Duct)	2750CFM*
Air Outlet (Options)	One 16" / One 18" / Two 12"
Air Inlet	Ductable 16"
Efficiency	90%
Fan Rating	5000 CFM@2.65"
Finish	Powder Coated
Ignition	Direct Spark
Wheels	Two 16" Dia Puncture Proof

*Ideal conditions. Actual output depends on operating conditions.



- Powder coated shell for high impact resistance
- Lifting hook & fork pockets
- 16" recirculation duct attachment feature
- High efficiency stainless steel heat exchanger
- Accessible burner and controls - easy access doors
- 4 Safety shutdown controls (High limit switch, exhaust limit switch, air switch, flame rod)
- Quick change fuel supply - dual fuel selector valve for propane & natural gas