

**Super Quiet Generators**

Distributed By:


[www.onesourcerental.com](http://www.onesourcerental.com)


**SUPER QUIET GENERATORS**  
**T45**

**STANDARD FEATURES**

- Versatile solution for your worksite power needs
- Rental ready mobile generator package
- Heavy duty 4 cycle diesel engine
- User friendly control panel

**Specifications**

System Rating at 60 Hz	
Prime	36 kW / 45 kVA
Standby	40 kW / 50 kVA
System Power Output at Prime	
Available 3 phase voltage	208 / 220 / 240 / 440 / 480
Associated 3 phase amps (0.8 power factor)	125 / 118 / 108 / 59 / 54
1 phase power	28 kW
1 phase kVA	28 kVA
Available 1 phase voltage	120 / 240
Associated 1 phase amps (1.0 power factor)	234 / 117
Max amp rating (main breaker size)	150 A

# Super Quiet Generator T45

## Specifications


Engine	T45
Manufacturer	Isuzu
Model	4JG1TPV
Horsepower - prime (1,800 rpm)	58 hp (43.3 kWm)
Description	4 cylinder, 4-cycle, water cooled, OHV, in-line, direct injection
Bore & stroke	3.74 x 4.21 in. (95 mm x 107 mm)
Piston displacement	189 in <sup>3</sup> (3.1 L)
Compression ratio	18.6 : 1
Exhaust system	critical grade silencer
Monitoring gauges	oil pressure, water temperature, fuel level, battery voltage, hours
Coolant capacity - engine only	3 qts (2.8 L)
Cooling system	liquid cooled - rated to 105° F ambient

Fuel System										
Specification	#2 diesel									
Filter	fuel / water separator									
Capacity	64 gal (242 L)									
Tank and containment	internal fuel tank with 110% fluid spill containment									
Consumption and run time	<table border="0"> <tr> <td>Full load</td> <td>2.8 gal/hr (10.6 L/hr)</td> <td>23 hr</td> </tr> <tr> <td>3/4 load</td> <td>2.2 gal/hr (8.3 L/hr)</td> <td>29 hr</td> </tr> <tr> <td>Half load</td> <td>1.7 gal/hr (6.4 L/hr)</td> <td>38 hr</td> </tr> </table>	Full load	2.8 gal/hr (10.6 L/hr)	23 hr	3/4 load	2.2 gal/hr (8.3 L/hr)	29 hr	Half load	1.7 gal/hr (6.4 L/hr)	38 hr
Full load	2.8 gal/hr (10.6 L/hr)	23 hr								
3/4 load	2.2 gal/hr (8.3 L/hr)	29 hr								
Half load	1.7 gal/hr (6.4 L/hr)	38 hr								

System Controls and Distribution	
Engine governor	mechanical (+/- 2%)
Protection (safety shutdowns)	low oil pressure, high water temp., overcrank, overspeed, underspeed
Generator gauges	voltmeter, ammeter, dial type Hz meter
Receptacles, 120 V	2 Each 20 Amp GFCI Duplex
Receptacles, 240 V	2 Each 50 Amp Tempower T/L
Primary Distribution	5 lug terminals with mainline circuit breaker

Generator	
Manufacturer	Newage
Rating (0.8 power factor)	40 kW 3 Phase @ 480 / 240 V
Description	brushless, 4 pole, synchronous, single bearing
Insulation	Class H
Temperature rating	125° C rise over 40° C ambient
Automatic voltage regulator	external, solid state, adjustable
Voltage regulation	+/- 1%
Frequency (speed)	60 Hz (1,800 rpm)

Packaging					
Enclosure	sound attenuated, weatherproof with lockable doors				
Sound levels	65 dBA at 23 ft (7 m)				
Lifting system	roof mounted, single point				
Weight (no trailer)	<table border="0"> <tr> <td>empty</td> <td>2,725 lbs (1,236 kg)</td> </tr> <tr> <td>full</td> <td>3,173 lbs (1,439 kg)</td> </tr> </table>	empty	2,725 lbs (1,236 kg)	full	3,173 lbs (1,439 kg)
empty	2,725 lbs (1,236 kg)				
full	3,173 lbs (1,439 kg)				
Dimensions - L x W x H (no trailer)	84 x 39 x 51 in (213 x 99 x 130 cm)				
Weight (with trailer)	<table border="0"> <tr> <td>empty</td> <td>3,200 lbs (1,452 kg)</td> </tr> <tr> <td>full</td> <td>3,648 lbs (1,655 kg)</td> </tr> </table>	empty	3,200 lbs (1,452 kg)	full	3,648 lbs (1,655 kg)
empty	3,200 lbs (1,452 kg)				
full	3,648 lbs (1,655 kg)				
Dimensions - L x W x H (with trailer)	137 x 66 x 68 in (348 x 168 x 173 cm)				



For more information, product demonstration, or details on purchase, lease and rental plans, please contact your local Genie distributor.



### Genie Industries, Inc.

A Terex Company

18340 NE 76th Street  
PO Box 97030  
Redmond, WA 98073-9730

TEL +1 (425) 881-1800  
TOLL FREE +1 (800) 536-1800  
PARTS & TECH SUPPORT +1 (800) 228-6444  
FAX +1 (425) 883-3475  
WEB [www.genieindustries.com](http://www.genieindustries.com)

### Distributed By:



[www.onesourcerental.com](http://www.onesourcerental.com)

Effective Date: January, 2008. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade-names of Terex Corporation, Genie Industries, Inc. and/or their subsidiaries in the U.S.A. and many other countries. All rights are reserved. Terex® is a registered trademark of Terex Corporation in the U.S.A. and many other countries. Genie® is a registered trademark of Genie Industries, Inc. in the U.S.A. and many other countries. Genie is a Terex Company. © 2008 Terex Corporation.