



These circulators should be used in clean and dry commercial applications - such as schools, shops, offices or warehouses.

Commercial Circulator

Motor, blades, guards, and mount are packed and shipped in a single UPS-able carton.



WALL MOUNT

Features

- Pull chain switch.
- SJT type 3 conductor, 9' long cord.
- Coated steel guards with retaining clips.
- Steel hub/spider aluminum paddle blades.
- Pole adjusts center of fan from 43" to 60".
- Meets OSHA standards.
- 1 Year limited warranty.

Motor Specifications

- 1-Phase
- 1/4 HP, 1/3 HP on HD Models
- Ball bearing
- Open ventilated
- 120V
- 2 or 3-Speed
- Permanently lubricated
- Permanent split capacitor

Standard Models

UPC# 686334	MODEL	SIZE	TYPE	MOUNT TYPE	CFM			AMPS (HIGH)	WT. (LBS.)	LIST
					HIGH	MED	LOW			
870627	CACU 24-P	24"	Standard	Pedestal Mount	5400	4900	4300	2.3	63	350
870641	CACU 24-W			Wall Mount						
869744	CACU 30-P	30"		Pedestal Mount	6000	5500	4800	2.4	66	387
870634	CACU 30-W			Wall Mount						
876179	CACU 30-P-HD	30"	Heavy Duty	Pedestal Mount	10200	8100	6700	3.60	56	450

Note: Stocked models may differ in appearance from photograph

TPI Commercial Oscillating Fans

Commercial wall mount and pedestal fans now available from TPI.

Standard Models



UPC# 686334	MODEL	SIZE	TYPE	MOUNT TYPE	CFM			AMPS			WT. (LBS.)	LIST
					HIGH	MED	LOW	HIGH	MED	LOW		
874892	CACU 24-PO	24"	Standard	Pedestal Mount	7500	6060	4050	1.45	1.15	1.1	68	410
874915	CACU 24-WO			Wall Mount								
874908	CACU 30-PO	30"		Pedestal Mount	8700	7500	6780	2.0	1.8	1.6	70	430
874922	CACU 30-WO			Wall Mount								
876186	CACU 30-PO-HD	30"	Heavy Duty	Pedestal Mount	10200	8100	6700	2.94	3.02	3.60	64	550

Note: Stocked models may differ in appearance from photograph - sizes are nominal.